

ViewSonic® Projectors

May / June 2013

With a 25-year heritage as an award-winning display technology leader, ViewSonic is poised to provide the best in complete projector solutions. Offering a broad range of product lines and breakthrough technologies, ViewSonic delivers an unbeatable user experience. Whether you are looking for a price-performance model for everyday use, network connectivity, or a high brightness solution, ViewSonic has the projector to perfectly fit any environment or budget. All ViewSonic projectors come standard with one of the best warranties in the industry, while individual product lines offer unique options to meet your specific needs



- 3-Year** Parts and labor limited warranty
- 1-Year** Free Express Exchange® Service*
- 1-Year** Limited lamp warranty



Professional

Product	Brightness / Contrast	Display Size @ Aspect Ratio	Resolution	Minimum Throw / Ratio	Lamp Type / Life (hrs.)**	Audio	ACT	120Hz 3D ready	VGA In / Out	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
PJL9371 3LCD	4,000 lm / 2,000:1	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	35" 1.5–1.8:1	260 W / 3,000/5,000	8W (x2)	–	–	2 / 1	S-video, component (DB–15) [†] , composite, audio x2, RS-232	9.5 lb	9.5 x 3.9 x 12.5	390W (typ)	Auto Vertical Keystone Manual zoom / focus
Pro8200 DLP®	2,000 lm / 4,000:1	30–300 in. @ 16:9 aspect ratio	Full HD 1920 x 1080	36" 1.4–2.14:1	230 W / 4,000/6,000	10W (x2)	–	–	2 / 1	HDMI x2, S-video, component (DB–15) [†] , composite, audio x3, RS-232	8.5 lb	13.0 x 4.3 x 10.4	310W (typ)	Auto Vertical Keystone Wide 1.5x optical zoom lens 7-segment color wheel Soft case included
Pro8300 DLP®	3,000 lm / 4,000:1	30–300 in. @ 16:9 aspect ratio	Full HD 1920 x 1080	36" 1.4–2.14:1	230 W / 4,000/6,000	10W (x2)	–	–	2 / 1	HDMI x2, S-video, component (DB–15) [†] , composite, audio x3, RS-232	8.5 lb	13.1 x 4.3 x 10.4	310W (typ)	Auto Vertical Keystone Wide 1.5x optical zoom lens Soft case included
Pro8400 DLP®	4,000 lm / 3,000:1	30–300 in. @ 16:9 aspect ratio	Full HD 1920 x 1080	36" 1.4–2.14:1	280 W / 4,000/5,000	10W (x2)	–	–	2 / 1	HDMI x2, S-video, component (DB–15) [†] , composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.0 x 4.8 x 10.4	360W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included
Pro8450w DLP®	4,500 lm / 4,300:1	30–300 in. @ 16:10 aspect ratio	WXGA 1280 x 800	47" 1.46–2.2:1	280 W / 4,000/5,000	10W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB–15) [†] , composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.1 x 4.8 x 10.4	350W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included
Pro8500 DLP®	5,000 lm / 4,900:1	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	47" 1.45–2.18:1	280 W / 4,000/5,000	10W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB–15) [†] , composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.1 x 4.8 x 10.4	350W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included
NEW! Pro8520HD DLP®	5,000 lm / 8,000:1	30–300 in. @ 16:9 aspect ratio	Full HD 1920 x 1080	36" 1.4–2.14:1	350 W / 2,500/3,000	10W (x2)	–	–	2 / 1	HDMI x2, S-video, component (DB–15) [†] , composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.1 x 4.8 x 10.4	450W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included
NEW! Pro8600 DLP®	6,000 lm / 15,000:1 ^{††}	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	36" 1.45–2.18:1	350 W / 2,500/3,000	10W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB–15) [†] , composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.1 x 4.8 x 10.4	408W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included
Pro9000 Laser/LED Hybrid DLP®	1,600 lm / 100,000:1	38–150 in. @ 16:9 aspect ratio	Full HD 1920 x 1080	59" 1.5–1.8:1	Laser/LED hybrid > 20,000	2W (x2)	–	–	1 / 0	HDMI x2, S-video, component (DB–15) [†] , composite, audio, RS-232	9.4 lb	12.6 x 5.3 x 10.2	<186W (typ)	Lamp-free design Vertical keystone correction Manual zoom / focus Soft case included

Sales: (888) 881-8781 • salesinfo@ViewSonic.com • ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running Eco-mode or whisper-mode exclusively can extend lamp life. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-01B-04/13]



High Performance

NEW!

NEW!

Product	Brightness / Contast	Display Size	Resolution	Minimum Throw / Ratio	Lamp Type / Life (hrs.)**	Audio	ACT	120Hz 3D ready	VGA In / Out	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
PJD7333 DLP®	4,000 lm / 15,000:1††	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	47" 1.39–2.23:1	330 W / 2,500/3,500	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RS-232, RJ45, USB	6.7 lb	13.2 x 5.1 x 10.4	350W (typ)	Content over IP Optional wireless Wide 1.6x optical zoom lens Soft case included
PJD7533w DLP®	4,000 lm / 15,000:1††	30–300 in. @ 16:10 aspect ratio	WXGA 1280 x 800	47" 1.47–1.83:1	330 W / 2,000/3,500	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RJ45, USB, RS-232	6.7 lb	13.2 x 5.1 x 10.4	350W (typ)	Content over IP Optional wireless Wide 1.6x optical zoom lens Soft case included
PJD7820HD DLP®	3,000 lm / 15,000:1††	30–300 in. @ 16:9 aspect ratio	Full HD 1920 x 1080	30" 1.15–1.5:1	210 W / 4,000/6,000	2W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio, RS-232	4.6 lb	10.6 x 3.3 x 8.7	260W (typ)	Vertical keystone correction Manual zoom / focus

Networkable

Product	Brightness / Contast	Display Size	Resolution	Minimum Throw / Ratio	Lamp Type / Life (hrs.)**	Audio	ACT	120Hz 3D ready	VGA In / Out	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
PJD6223 DLP®	2,700 lm / 15,000:1††	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	47" 1.86–2.04:1	180 W / 5,000/6,000	10W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RS-232, RJ45	5.7 lb	11.6 x 3.3 x 9.5	250W (typ)	Vertical keystone correction Manual zoom / focus LAN monitoring & control
PJL6233 3LCD	2,600 lm / 500:1	40–300 in. @ native 4:3 ratio	XGA 1024 x 768	51" 1.62–1.92:1	215 W / 4,000/6,000	1W (x1)	–	–	2 / 1	S-video, component (DB–15)†, composite, audio x2, RS-232, RJ45	5.7 lb	13.4 x 4.2 x 9.9	284W (typ)	Auto vertical keystone Manual zoom / focus LAN monitoring & control
PJD6235 DLP®	3,000 lm / 15,000:1††	24–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	36" 1.86–2.04:1	190 W / 4,500/6,000	2W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio, RS-232, RJ45	4.6 lb	10.5 x 3.3 x 8.7	240W (typ)	Vertical keystone correction Manual zoom / focus LAN monitoring & control
PJD6245 DLP®	3,000 lm / 15,000:1††	24–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	36" 1.86–2.04:1	190 W / 4,500/6,000	2W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio, RS-232, RJ45	4.6 lb	10.6 x 3.3 x 8.7	240W (typ)	Vertical keystone correction Manual zoom / focus LAN monitoring & control
PJD6345 DLP®	3,500 lm / 15,000:1††	28–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	47" 1.97–2.17:1	240 W / 3,500/5,000	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RS-232, RJ45, USB	4.7 lb	11.6 x 4.5 x 8.6	305W (typ)	Content over IP Optional wireless Vertical keystone correction Manual zoom / focus
PJD6353s DLP®	2,500 lm / 15,000:1††	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	15" 0.61:1	180 W / 5,000/6,000	10W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RS-232	6.6 lb	11.6 x 3.3 x 9.5	310W (typ)	Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control
PJD6383s DLP®	3,000 lm / 15,000:1††	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	15" 0.61:1	240 W / 3,500/5,000	10W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RS-232	6.6 lb	11.6 x 3.3 x 9.5	310W (typ)	Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control

NEW!

Sales: (888) 881-8781 • salesinfo@ViewSonic.com • ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running Eco-mode or whisper-mode exclusively can extend lamp life. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-01B-04/13]

Networkable

Product	Brightness / Contrast	Display Size	Resolution	Minimum Throw / Ratio	Lamp Type / Life (hrs.)**	Audio	ACT	120Hz 3D ready	VGA In / Out	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
PJD6543w DLP®	3,000 lm / 15,000:1††	28–300 in. @ native 16:10 ratio	WXGA 1280 x 800	36" 1.5–1.65:1	190 W / 4,500/6,000	1x2W	–	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio, RJ45, RS-232	4.6 lb	10.6 x 3.3 x 8.7	240W (typ)	Vertical keystone correction Manual zoom / focus LAN monitoring & control
PJD6544w DLP®	3,500 lm / 15,000:1††	28–300 in. @ native 16:10 ratio	WXGA 1280 x 800	47" 1.47–1.83:1	240 W / 3,500/5,000	1x16W	Yes	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, USB, RS-232	4.7 lb	11.6 x 4.5 x 8.6	305W (typ)	Content over IP Optional wireless Vertical keystone correction Manual zoom / focus
PJD6683ws DLP®	3,000 lm / 15,000:1††	30–300 in. @ 16:10 aspect ratio	WXGA 1280 x 800	12" 0.5:1	240 W / 3,500/5,000	10W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232	6.6 lb	11.6 x 3.3 x 9.5	310W (typ)	Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control
PJD7333 DLP®	4,000 lm / 15,000:1††	30–300 in. @ native 4:3 ratio	XGA 1024 x 768	47" 1.39–2.23:1	330 W / 2,500/3,500	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232, RJ45, USB	6.7 lb	13.2 x 5.1 x 10.4	350W (typ)	Content over IP Optional wireless Wide 1.6x optical zoom lens Soft case included
PJD7533w DLP®	4,500 lm / 15,000:1††	30–300 in. @ native 16:10 ratio	WXGA 1280 x 800	47" 1.47–1.83:1	330 W / 2,000/3,500	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, USB, RS-232	6.7 lb	13.2 x 5.1 x 10.4	350W (typ)	Content over IP Optional wireless Wide 1.6x optical zoom lens Soft case included
PJD8333s DLP®	3,000 lm / 15,000:1††	60–250 in. @ 4:3 aspect ratio	XGA 1024 x 768	19" 0.468:1	240 W / 3,500/5,000	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232, RJ45, USB	8.0 lb	13.2 x 5.1 x 10.4	350W (typ)	Content over IP Optional wireless Vertical keystone correction Soft case included
PJD8353s Interactive DLP®	3,000 lm / 15,000:1††	47–150 in. @ 4:3 aspect ratio	XGA 1024 x 768	20" 0.43:1	240 W / 3,500/5,000	8W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x4, RS-232, RJ45, USB	16.1 lb	14.1 x 9.9 x 14.4	300W (typ)	Optional dual interactive pens Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control
PJD8633ws DLP®	3,000 lm / 15,000:1††	60–250 in. @ 16:10 aspect ratio	WXGA 1280 x 800	19" 0.375:1	240 W / 3,500/5,000	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232, RJ45, USB	8.0 lb	13.2 x 5.1 x 10.4	350W (typ)	Content over IP Optional wireless Vertical keystone correction Soft case included
PJD8653ws Interactive DLP®	3,000 lm / 15,000:1††	47–150 in. @ 16:10 aspect ratio	WXGA 1280 x 800	20" 0.35:1	240 W / 3,500/5,000	8W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x4, RS-232, RJ45, USB	16.1 lb	14.1 x 9.9 x 14.4	300W (typ)	Optional dual interactive pens Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control
Pro8400 DLP®	4,000 lm / 3,000:1	30–300 in. @ 16:9 aspect ratio	Full HD 1920 x 1080	36" 1.4–2.14:1	280 W / 4,000/5,000	10W (x2)	–	–	2 / 1	HDMI x2, S-video, component (DB-15)†, composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.0 x 4.8 x 10.4	360W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included
Pro8450w DLP®	4,000 lm / 4,300:1	30–300 in. @ 16:10 aspect ratio	WXGA 1280 x 800	47" 1.46–2.2:1	280 W / 4,000/5,000	10W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB-15)†, composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.1 x 4.8 x 10.4	350W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included

Sales: (888) 881-8781 • salesinfo@ViewSonic.com • ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running Eco-mode or whisper-mode exclusively can extend lamp life. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-01B-04/13]

Networkable

Product	Brightness / Contast	Display Size	Resolution	Minimum Throw / Ratio	Lamp Type / Life (hrs.)**	Audio	ACT	120Hz 3D ready	VGA In / Out	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
Pro8500 DLP®	5,000 lm / 4,900:1	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	47" 1.45–2.18:1	280 W / 4,000/5,000	10W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.1 x 4.8 x 10.4	350W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included
NEW! Pro8520HD DLP®	5,000 lm / 8,000:1	30–300 in. @ 16:9 aspect ratio	Full HD 1920 x 1080	36" 1.4–2.14:1	350 W / 2,500/3,000	10W (x2)	–	–	2 / 1	HDMI x2, S-video, component (DB–15)†, composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.1 x 4.8 x 10.4	450W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included
NEW! Pro8600 DLP®	6,000 lm / 15,000:1††	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	36" 1.45–2.18:1	350 W / 2,500/3,000	10W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x3, RJ45, USB, RS-232	8.5 lb	13.1 x 4.8 x 10.4	408W (typ)	Auto vertical keystone Wide 1.5x optical zoom lens Content over IP Soft case included

Short / Ultra Short Throw

Product	Brightness / Contast	Display Size	Resolution	Minimum Throw / Ratio	Lamp Type / Life (hrs.)**	Audio	ACT	120Hz 3D ready	VGA In / Out	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
PJD6353s DLP®	2,500 lm / 15,000:1††	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	15" 0.61:1	180 W / 5,000/6,000	10W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RJ45, RS-232	6.6 lb	11.6 x 3.3 x 9.5	310W (typ)	Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control
PJD6383s DLP®	3,000 lm / 15,000:1††	30–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	15" 0.61:1	240 W / 3,500/5,000	10W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RJ45, RS-232	6.6 lb	11.6 x 3.3 x 9.5	310W (typ)	Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control
PJD6683ws DLP®	3,000 lm / 15,000:1††	30–300 in. @ 16:10 aspect ratio	WXGA 1280 x 800	12" 0.5:1	240 W / 3,500/5,000	10W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RJ45, RS-232	6.6 lb	11.6 x 3.3 x 9.5	310W (typ)	Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control
NEW! PJD8333s DLP®	3,000 lm / 15,000:1††	60–250 in. @ 4:3 aspect ratio	XGA 1024 x 768	19" 0.468:1	240 W / 3,500/5,000	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RS-232, RJ45, USB	8.0 lb	13.2 x 5.1 x 10.4	350W (typ)	Content over IP Optional wireless Vertical keystone correction Soft case included
PJD8353s Interactive DLP®	3,000 lm / 15,000:1††	47–150 in. @ 4:3 aspect ratio	XGA 1024 x 768	20" 0.43:1	240 W / 3,500/5,000	8W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x4, RS-232, RJ45, USB	16.1 lb	14.1 x 9.9 x 14.4	300W (typ)	Optional dual interactive pens Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control
NEW! PJD8633ws DLP®	3,000 lm / 15,000:1††	60–250 in. @ 16:10 aspect ratio	WXGA 1280 x 800	19" 0.375:1	240 W / 3,500/5,000	16W (x1)	Yes	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x2, RS-232, RJ45, USB	8.0 lb	13.2 x 5.1 x 10.4	350W (typ)	Content over IP Optional wireless Vertical keystone correction Soft case included
PJD8653ws Interactive DLP®	3,000 lm / 15,000:1††	47–150 in. @ 16:10 aspect ratio	WXGA 1280 x 800	20" 0.35:1	240 W / 3,500/5,000	8W (x2)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio x4, RS-232, RJ45, USB	16.1 lb	14.1 x 9.9 x 14.4	300W (typ)	Optional dual interactive pens Vertical keystone correction Digital zoom w/ manual focus LAN monitoring & control

Sales: (888) 881-8781 • salesinfo@ViewSonic.com • ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running Eco-mode or whisper-mode exclusively can extend lamp life. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-01B-04/13]

Portable

Product	Brightness / Contast	Display Size	Resolution	Minimum Throw / Ratio	Lamp Type / Life (hrs.)**	Audio	ACT	120Hz 3D ready	VGA In / Out	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
PLED-W200 LED with DLP®	250 lm / 2,000:1	24–80 in. @ 16:10 aspect ratio	WXGA 1280 x 800	24" 1.16:1	LED > 20,000	2W (x2)	–	Yes	1 / 0	Component (DB–15)†, composite, audio, USB	0.9 lb	5.1 x 1.3 x 5.0	< 50W (typ)	Auto vertical keystone Digital zoom w/ manual focus Soft case included
PLED-W500 LED with DLP®	500 lm / 6,000:1	30–100 in. @ 16:10 aspect ratio	WXGA 1280 x 800	35" 1.4:1	LED > 20,000	2W (x1)	–	Yes	1 / 0	HDMI, S-video, Component (DB–15)†, composite, audio, USB, SD, Memory (1GB)	2.6 lb	8.4 x 1.6 x 6.4	< 50W (typ)	Auto vertical keystone Digital zoom w/ manual focus Soft case included

Price Performance

Product	Brightness / Contast	Display Size	Resolution	Minimum Throw / Ratio	Lamp Type / Life (hrs.)**	Audio	ACT	120Hz 3D ready	VGA In / Out	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
PJD5126 DLP®	2,700 lm / 15,000:1††	30–300 in. @ 4:3 aspect ratio	SVGA 800 x 600	47" 1.86–2.04:1	180 W / 5,000/6,000	2W (x1)	–	Yes	2 / 1	S-video, component (DB–15)†, composite, audio, RS-232	5.7 lb	11.6 x 3.3 x 9.5	243W (typ)	Vertical keystone correction Manual zoom / focus
PJD5132 DLP®	3,000 lm / 15,000:1††	24–300 in. @ 4:3 aspect ratio	SVGA 800 x 600	40" 1.86–2.04:1	190 W / 4,500/6,000	2W (x1)	–	Yes	2 / 1	S-video, component (DB–15)†, composite, audio, RS-232	4.6 lb	10.6 x 3.3 x 8.7	250W (typ)	Vertical keystone correction Manual zoom / focus
PJD5134 DLP®	3,000 lm / 15,000:1††	24–300 in. @ 4:3 aspect ratio	SVGA 800 x 600	40" 1.86–2.04:1	190 W / 4,500/6,000	2W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio, RS-232	4.6 lb	10.6 x 3.3 x 8.7	250W (typ)	Vertical keystone correction Manual zoom / focus
PJD5223 DLP®	2,700 lm / 3,000:1	27–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	47" 1.97–2.17:1	180 W / 5,000/6,000	2W (x1)	–	Yes	2 / 1	S-video, component (DB–15)†, composite, audio, RS-232	5.7 lb	11.2 x 3.2 x 9.2	235W (typ)	Vertical keystone correction Manual zoom / focus
PJD5232 DLP®	2,800 lm / 15,000:1††	24–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	39" 1.97–2.17:1	190 W / 5,000/6,000	2W (x1)	–	Yes	2 / 1	S-video, component (DB–15)†, composite, audio, RS-232	4.7 lb	11.6 x 3.7 x 8.0	245W (typ)	Vertical keystone correction Manual zoom / focus
PJD5234 DLP®	2,800 lm / 15,000:1††	24–300 in. @ 4:3 aspect ratio	XGA 1024 x 768	39" 1.97–2.17:1	190 W / 5,000/6,000	2W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio, RS-232	4.7 lb	11.6 x 3.7 x 8.0	245W (typ)	Vertical keystone correction Manual zoom / focus
PJD5533w DLP®	3,000 lm / 15,000:1††	28–300 in. @ 16:10 aspect ratio	WXGA 1280 x 800	39" 1.5–1.65:1	190 W / 5,000/6,000	2W (x1)	–	Yes	2 / 1	HDMI, S-video, component (DB–15)†, composite, audio, RS-232	4.6 lb	10.6 x 3.3 x 8.7	240W (typ)	Vertical keystone correction Manual zoom / focus

Sales: (888) 881-8781 • salesinfo@ViewSonic.com • ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running Eco-mode or whisper-mode exclusively can extend lamp life. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-01B-04/13]



Projector Replacement Lamps

ViewSonic offers longlife, user-installable replacement lamps for all our projectors.

Projector Replacement Lamps

Model #	Lamp for:	Model #	Lamp for:	Model #	Lamp for:
RLC-025	PJ258D	RLC-051	PJD6251	RLC-072	PJD5123, PJD5133, PJD5223, PJD5233, PJD5523w, PJD5353
RLC-026	PJ588D	RLC-052	PJD2121	RLC-075	PJD6243
RLC-027	PJ358	RLC-053	PJL9371	RLC-076	Pro8520HD, Pro8600
RLC-030	PJ503D	RLC-054	PJD7211	RLC-077	PJD5226
RLC-031	PJ759	RLC-055	PJD5122, PJD5352, PJD5352	RLC-078	PJD5132, PJD5134, PJD6235, PJD6245
RLC-034	PJ551D, PJ557D, PJD6220	RLC-057	PJD7382, PJD7383, PJD7583w, PJD7383i, PJD7583wi	RLC-079	PJD7820HD
RLC-037	PJ560D, PJ6240	RLC-059	Pro8450w, Pro8500, Pro8400	RLC-080	PJD8333s, PJD8633ws
RLC-038	PJ1173	RLC-061	Pro8200, Pro8300	RLC-081	PJD7333, PJD7533w
RLC-039	PJ359w, PJL3211	RLC-063	Pro9500	RLC-082	PJD8353s, PJD8653ws
RLC-047	PJD5351	RLC-065	PJL6233, PJL6243	RLC-083	PJD5232, PJD5234
RLC-049	PJD6381, PJD6241, PJD6531w	RLC-070	PJD5126, PJD6223, PJD6353s	RLC-084	PJD6345, PJD6544w
RLC-050	PJD5112, PJD6211, PJD6221, PJD6531w	RLC-071	PJD6253, PJD6553w, PJD6383s, PJD6683ws	RLC-085	PJD5533w, PJD6543w

Projector Mounts and Accessories

Model #	Description
WMK-005	Universal Ceiling Mount (not compatible with 2lb. projectors)
WMK-027	Short Throw Wall Mount (short throw projectors)
WMK-042	Ultra Short Throw Wall Mount (ultra short throw projectors)
PJ-PEN-003	Interactive Pen / Camera Kit (for PJD8353s, PJD8653ws)
WPD-100	Wireless USB Adapter (for ACT models, Pro8400, Pro8450w, Pro8500, Pro8520HD, Pro8600)
WPG-360	Wireless Presentation Gateway

Sales: (888) 881-8781 • salesinfo@ViewSonic.com • ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running Eco-mode or whisper-mode exclusively can extend lamp life. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-01B-04/13]



3+1+1 Warranty

ViewSonic's industry-leading warranty that provides 3-year limited parts and labor, 1-year lamp, and first year free Express Exchange® Service.**



3-D Ready

With support for DLP Link Technology, ViewSonic projectors are capable of projecting 3D images.



3LCD

Three-panel LCD is a transmissive technology that uses color-specific LCD panels to reproduce rich, vibrant images with excellent color saturation that does not vary with image brightness.



Advanced Connect Technology (ACT)

ViewSonic projectors that are equipped with Advanced Connect Technology have the capability to display presentations over a wired or wireless LAN, via USB port, directly from a USB flash drive, or from smart phones and tablets using a mobile app.



DLP (Digital Light Processing)

All DLP projections stem from a Texas Instruments DLP microchip that manipulates light and color via several hundred thousand microscopic mirrors located on the surface of the chip. Spaced less than one micron apart, these mirrors produce a smooth, crystal-clear image.



Eco-mode

A function found on ViewSonic projectors that can extend the life of the projector lamp by almost 50%, and up to 5,000 hours in some cases. Other benefits of Eco-mode operation include reduced power consumption, as well as less heat and audible noise output.



Filter-Free Design

Unlike LCD projectors that require users to clean, or sometimes replace, filters every 100 to 300 hours of operation, ViewSonic's filter-less design eliminates filter cleaning or filter replacement. This provides virtually zero maintenance, saves you significant dollars and labor over the projector's lifespan, and lowers your total cost of ownership (TCO).



HDMI

(High Definition Multimedia Interface)

HDMI provides future-proof connectivity and is the highest standard for transferring video and audio data from an HDMI-compliant device to a compatible monitor, projector, television, or digital audio device.



Keystone Correction

When images are projected onto a surface at an angle, the image may be distorted and will be displayed in the shape of a trapezoid, or "keystone". Keystone Correction is a function of ViewSonic projectors that automatically adjusts and straightens distorted images so that they display properly.



Long Lamp Life

ViewSonic's highly efficient long-life lamps can last up to 10,000 hours when in DynamicEco mode. This greatly extends the projector's life and reduces frequent, costly lamp replacements. ViewSonic projectors with long-life lamps are perfect for use in businesses and schools, where efficiency, quality and cost savings are key.



Reliable Color Performance

Built on DLP technology, ViewSonic projectors virtually eliminate image degradation known as color decay – a yellow/faded tint that LCD projectors may develop after extended use. Even after years of use, the projectors will continue to produce stunning, sharp images that last.



Wide Optical Zoom Lens

With a wider throw distance range, wide optical zoom lenses provide mounting flexibility to reduce installation hassles. These zoom lenses also enable the projector to project images up to 50% larger than a conventional model equipped with a standard 1.1x lens.